

Integrated 3D Dozer System

3D-MC^{MAX}



Redefine the capabilities of
your dozer

Integrated 3D Dozer System

3D-MC^{MAX}

A revolutionary dozing system, 3D-MC^{MAX} delivers the highest productivity dozer solution for any rough or fine grading application. 3D-MC^{MAX} uses our industry leading MC²⁺ IMU sensors on the body and blade as well as an optional third IMU on the C-frame – all to keep the blade cutting edge on grade for any application. This system was built to keep you productive on any job site – providing maximum speed, maximum control, and maximum performance.

Slim and trim – a clear path ahead

The power of the system lies within the IMU sensors. These robust and highly precise sensors work together with ruggedized cab-mounted antennas conveniently placed in a secure location on the machine. This intelligent design gives the operator unobstructed visibility and the flexibility to doze at full throttle on any surface, under objects, or while in reverse.

Any application, anywhere

The 3D-MC^{MAX} system can be used for fine grading applications such as those traditionally done by motor graders. With support for 4-way, 6-way, and pitch controlled blades, any dozer operation can benefit from a 3D-MC^{MAX} system. The MC²⁺ IMU sensors work together to keep the blade as close to the surface as possible, delivering a smooth and consistent pass for any slope.

Single or dual antenna configurations

Support for 4-way, 6-way, and pitch controlled blades

Eliminates the need for GNSS mast

Superior performance for any rough or fine grading job site application

Increased blade response

Accurate as-built data for volume and productivity reporting





- 1 Dual GNSS antennas
 - 2 Radio antenna
 - 3 GX-55 control box
 - 4 MC-R3 GNSS receiver
- 5 On-blade MC2+ IMU sensor
 - 6 Optional C-Frame MC2+ IMU sensor
 - 7 On-body MC2+ IMU sensor

Outperform the field with the 3D-MC^{MAX} system. It takes advantage of every movement made when the machine is in motion and allows you to cut finish grade while driving in reverse at high speeds. The results – a substantial increase in your productivity.

3D-MC machine control software

The GX-55 control box is intuitive and modern, our machine control software seamlessly drives all components in the 3D-MC^{MAX} system.



Visualize your every movement and have the integrated LED light bars guide you when you're on grade.



Rapid blade response technology

Built tough for any environment, the MC²+ IMU sensors mounted on the body and blade deliver update rates to the system keeping the blade on grade at high speeds.



Intuitive control box

The robust design of the GX-55 control box is delivered in a lightweight, compact aluminum housing – complete with integrated LED light bars, a graphical interface and fast data processor.



Versatile motion control interface

The MC-R3 is an interchangeable receiver with integrated boards for GNSS, radio, and controller to receive RTK corrections as well as drive valves of the machine.



Fence Antenna™ technology

Conveniently mounted on the cab of the machine, the MC-G3 antenna captures all available GNSS satellite signals while identifying and rejecting signal noise – for ultimate grade control.



Specifications subject to change without notice.
© 2021 Topcon Corporation. All rights reserved.
7010-2202 C 3/21

www.topconpositioning.com/3dmcmx

